

- 2 -

Ser. No. 09/715,275

IN THE CLAIMS

Please cancel claims 1-4, 6-14, 19-24, 26-49, 52-65, and 67-72.

1. (cancelled)
2. (cancelled)
3. (cancelled)
4. (cancelled)
5. (previously cancelled)
6. (cancelled)
7. (cancelled)
8. (cancelled)
9. (cancelled)
10. (cancelled)
11. (cancelled)
12. (cancelled)

H:\Heidi\EA\optics\AMD\$004.812.frm

- 3 -

Ser. No. 09/715,275

13. (cancelled)
14. (cancelled)
15. (previously cancelled)
16. (previously cancelled)
17. (previously cancelled)
18. (previously cancelled)
19. (cancelled)
20. (cancelled)
21. (cancelled)
22. (cancelled)
23. (cancelled)
24. (cancelled)
25. (previously cancelled)

H:\Heidi\EVALoptics\AMD\$004.B12.frm

- 4 -

Ser. No. 09/715,275

- 26. (cancelled)
- 27. (cancelled)
- 28. (cancelled)
- 29. (cancelled)
- 30. (cancelled)
- 31. (cancelled)
- 32. (cancelled)
- 33. (cancelled)
- 34. (cancelled)
- 35. (cancelled)
- 36. (cancelled)
- 37. (cancelled)
- 38. (cancelled)

H:\Held\EI\Alloptic\AMD\$004,812.frm

- 5 -

Ser. No. 09/715,275

- 39. (cancelled)
- 40. (cancelled)
- 41. (cancelled)
- 42. (cancelled)
- 43. (cancelled)
- 44. (cancelled)
- 45. (cancelled)
- 46. (cancelled)
- 47. (cancelled)
- 48. (cancelled)
- 49. (cancelled)
- 50. (previously cancelled)
- 51. (previously cancelled)

H:\HeldiE\Alloptic\AMD\$004.B12.fm

- 6 -

Ser. No. 09/715,275

52. (cancelled)

53. (cancelled)

54. (cancelled)

55. (cancelled)

56. (cancelled)

57. (cancelled)

58. (cancelled)

59. (cancelled)

60. (cancelled)

61. (cancelled)

62. (cancelled)

63. (cancelled)

64. (cancelled)

H:\HeidiE\Alloptic\AMD\$004.812.frm

- 7 -

Ser. No. 09/715,275

65. (cancelled)

66. (previously cancelled)

67. (cancelled)

68. (cancelled)

69. (cancelled)

70. (cancelled)

71. (cancelled)

72. (cancelled)

73. (previously added) A point-to-multipoint optical communications system comprising:

an optical line terminal (OLT); and

a plurality of optical network units (ONUs) connected to said OLT by a passive optical network in which downstream data is transmitted from said OLT to said ONUs over said passive optical network and upstream data is transmitted from said ONUs to said OLT over said passive optical network;

said OLT transmitting downstream data over said passive optical network in variable-length downstream packets;

H:\Held\EI\AllOptic\AMD\$004.B12.frm

- 8 -

Ser. No. 09/715,275

said ONUs transmitting downstream data over said passive optical network within ONU-specific time slots utilizing time division multiplexing, wherein said ONU-specific time slots are filled with multiple variable-length upstream packets;

said OLT includes:

a fragment buffer for storing packet fragments that have been transmitted upstream from said ONUs; and

fragment logic for:

identifying said end-of-packet-fragment code of said first packet fragment;

buffering said first packet fragment in said OLT fragment buffer;

identifying said start-of-packet-fragment code of said first packet fragment;

reconstructing said variable-length upstream packet from said first and second packet fragments;

said ONUs include:

fragment buffers for storing packet fragments that are to be transmitted upstream from said ONUs; and

fragment logic for:

splitting a variable-length upstream packet into first and second packet fragments; and

adding an end-of-packet-fragment code to said first packet fragment and adding a start-of-packet-fragment code to said second packet fragment.

74. (previously added) The system of claim 73 wherein said variable-length downstream packets are formatted according to IEEE 802.3.

75. (previously added) The system of claim 73 wherein said variable-length downstream packets include Internet protocol (IP) datagrams.

76. (previously added) The system of claim 75 wherein the lengths of said variable-length downstream packets include the lengths of said IP datagrams plus packet overhead.

77. (previously added) The system of claim 73 wherein said variable-length upstream packets include Internet protocol (IP) datagrams.

78. (previously added) The system of claim 77 wherein the lengths of said variable-length upstream packets include the lengths of said IP datagrams plus packet overhead.

79. (previously added) The system of claim 73 wherein:

said variable-length downstream packets and said variable-length upstream packets are formatted according to IEEE 802.3; and

said downstream data and said upstream data include Internet protocol (IP) datagrams.

80. (previously added) A method for exchanging information between an optical line terminal (OLT) and multiple optical network units (ONUs) in a point-to-multipoint passive optical network comprising:

- 10 -

Ser. No. 09/715,275

transmitting downstream data from said OLT to said ONUs in variable-length downstream packets;

transmitting upstream data from said ONUs to said OLT in ONU-specific time slots utilizing time division multiplexing to avoid transmission collisions, wherein said ONU-specific time slots are filled with multiple variable-length upstream packets;

splitting a variable-length upstream packet into a first packet fragment and a second packet fragment;

adding an end-of-packet-fragment code to the end of said first packet fragment;

adding a start-of-packet-fragment code to the start of said second packet fragment;

transmitting said first packet fragment upstream in a first ONU-specific time slot;

buffering said second packet fragment for transmission in a second ONU-specific time slot that is different from said first ONU-specific time slot;

buffering said first packet fragment after said first packet fragment is received at said OLT; and

reconstructing said variable-length upstream packet, at said OLT, from said first packet fragment and said second packet fragment.

81. (previously added) The system of claim 80 wherein said variable-length downstream and upstream packets are formatted in accordance with IEEE 802.3 protocol.

82. (previously added) The method of claim 80 wherein said variable-length downstream and upstream packets include overhead and a payload, and wherein the length of each of said variable-length packets includes the length of an Internet protocol (IP) datagram that is included in the payload of each of said variable-length packets plus the packet overhead.

83. (previously added) A point-to-multipoint optical communications systems comprising:
an optical line terminal (OLT); and

a plurality of optical network units (ONUs) connected to said OLT by a passive optical network in which downstream data is transmitted from said OLT to said ONUs and upstream data is transmitted from said ONUs to said OLT;

said OLT including means for formatting downstream datagrams into variable-length downstream packets;

each of said ONUs including:

means for formatting upstream datagrams into variable-length upstream packets; and

means for timing the transmission of said variable-length upstream packets to coincide with ONU-specific time slots in order to avoid collisions with upstream packets from other ONUs, wherein said ONU-specific time slots are filled with multiple variable-length upstream packets;

said OLT includes:

a fragment buffer for storing packet fragments that have been transmitted upstream from said ONUs;

fragment logic for:

identifying said end-of-packet fragment code of said first packet fragment;

- 12 -

Ser. No. 09/715,275

buffering said first packet fragment in said OLT fragment buffer;

identifying said start-of-packet-fragment code of said second packet fragment; and

reconstructing said variable-length upstream packet from said first and second packet fragments;

said ONUs include:

fragment buffers for storing packet fragments that are to be transmitted upstream from said ONUs;

fragment logic for:

splitting a variable-length upstream packet into first and second packet fragments; and

adding an end-of-packet-fragment code to said first packet fragment and adding a start-of-packet-fragment code to said second packet fragment.

84. (previously added) The system of claim 83 wherein said variable-length downstream packets are formatted according to IEEE 802.3.

85. (previously added) The system of claim 83 wherein said downstream datagrams are Internet protocol (IP) datagrams.

86. (previously added) The system of claim 85 wherein the length of said variable-length downstream packets include the lengths of said IP datagrams plus packet overhead.

87. (previously added) The system of claim 83 wherein said upstream datagrams are Internet protocol (IP) datagrams.

H:\HeidiE\Alloptic\AMD\$004.B12.frm

88. (previously added) The system of claim 87 wherein the lengths of said variable-length upstream packets include the lengths of said IP datagrams plus packet overhead.

89. (previously added) The system of claim 83 wherein:

said variable-length downstream packets and said variable-length upstream packets are formatted according to IEEE 802.3; and

said downstream datagrams and said upstream datagrams are Internet protocol (IP) datagrams.

90. (previously added) A point-to-multipoint optical communications system comprising:

an optical line terminal (OLT); and

a plurality of optical network units (ONUs) connected to said OLT by a passive optical network in which downstream data is transmitted from said OLT to said ONUs over said passive optical network and upstream data is transmitted from said ONUs to said OLT over said passive optical network;

said OLT transmitting downstream data over said passive optical network in variable-length downstream packets;

said ONUs transmitting upstream data over said passive optical network within ONU-specific time slots utilizing time division multiplexing, wherein said ONU-specific time slots are filled with multiple variable-length upstream packets;

said OLT including a fragment buffer for storing packet fragments that have been transmitted upstream from said ONUs;

said ONUs including:

fragment buffers for storing packet fragments that are to be transmitted upstream from said ONUs;

fragment logic for splitting a variable-length upstream packet into first and second packet fragments, adding an end-of-packet-fragment

code to said first packet fragment, and adding a start-of-packet-fragment code to said second packet fragment;
said OLT includes fragment logic for:
 identifying said end-of-packet-fragment code of said first packet fragment;
 buffering said first packet fragment in said OLT fragment buffer;
 identifying said start-of-packet-fragment code of said second packet fragment; and
 reconstructing said variable-length upstream packet from said first and second packet fragments.

91. (previously added) The system of claim 90 wherein said variable-length downstream packets are formatted according to IEEE 802.3.

92. (previously added) The system of claim 90 wherein said variable-length downstream packets include Internet protocol (IP) datagrams.

93. (previously added) The system of claim 92 wherein the lengths of said variable-length downstream packets include the lengths of said IP datagrams plus packet overhead.

94. (previously added) The system of claim 90 wherein said variable-length upstream packets are formatted according to IEEE 802.3.

95. (previously added) The system of claim 90 wherein said variable-length upstream packets include Internet protocol (IP) datagrams.

H:\HeidiE\Alloptic\AMD\$004.B12.frm

96. (previously added) The system of claim 95 wherein the lengths of said variable-length upstream packets include the lengths of said IP datagrams plus packet overhead.

97. (previously added) The system of claim 90 wherein;

said variable-length downstream packets and said variable-length upstream packets are formatted according to IEEE 802.3; and

said downstream data and said upstream data include Internet protocol (IP) datagrams.

98. (previously added) A method of exchanging information between an optical line terminal (OLT) and multiple optical network units (ONUs) in a point-to-multipoint passive optical network comprising:

transmitting downstream data from said OLT to said ONUs in variable-length downstream packets;

transmitting downstream synchronization markers at constant time intervals;

transmitting upstream data from said ONUs to said OLT in ONU-specific time slots utilizing time division multiplexing to avoid transmission collisions, wherein said ONU-specific time slots are filled with variable-length upstream packets;

splitting a variable-length upstream packet into a first packet fragment and a second packet fragment;

adding an end-of-packet-fragment code to the end of said first packet fragment;

adding a start-of-packet-fragment code to the start of said second packet fragment;

transmitting said first packet fragment upstream in a first ONU-specific to time slot;

buffering said second packet fragment for transmission in a second ONU-specific time slot that is different from said first ONU-specific time slot;

buffering said first packet fragment after said first packet fragment is received at said OLT; and

reconstructing said variable-length upstream packet, at said OLT, from said first packet fragment and said second packet fragment.

99. (previously added) The method of claim 98 wherein said variable-length downstream and upstream packets are formatted in accordance with the IEEE 802.3 protocol.

100. (previously added) The method of claim 98 wherein said variable-length downstream and upstream packets include packet overhead and a payload, and wherein the length of each of said variable-length packets includes the length of an Internet protocol (IP) datagram that is included in the payload of each of said variable-length packets plus the packet overhead.

101. (previously added) The method of claim 98 wherein said ONU-specific time slots are filled with multiple variable-length packets according to IEEE 802.3 format.

102. (previously added) A method for exchanging information between an optical line terminal (OLT) and multiple optical network units (ONUs) in a point-to-multipoint passive optical network comprising:

transmitting downstream data from said OLT to said ONUs in variable-length downstream packets;

transmitting upstream data from said ONUs to said OLT in ONU-specific time slots utilizing time division multiplexing to avoid transmission collisions, wherein said ONU-specific time slots are filled with variable-length upstream packets;

splitting a variable-length upstream packet into a first packet fragment and a second packet fragment;

adding an end-of-packet-fragment code to the end of said first packet fragment;

adding a start-of-packet-fragment code to the start of said second packet fragment;

transmitting said first packet fragment upstream in a first ONU-specific time slot;

buffering said second packet fragment for transmission in a second ONU specific time slot that is different from said first ONU-specific time slot;

buffering said first packet fragment after said first packet fragment is received at said OLT; and

reconstructing said variable-length upstream packet, at said OLT, from said first packet fragment and said second packet fragment.

103. (previously added) The method of claim 102 wherein said variable-length downstream and upstream packets are formatted in accordance with the IEEE 802.3 protocol.

104. (previously added) The method of claim 102 wherein said variable-length downstream and upstream packets include packet overhead and a payload, and wherein the length of each of said variable-length packets includes the length of an Internet protocol (IP) datagram that is included in the payload of each of said variable-length packets plus the packet overhead.

H:\HeidiE\Alloptic\AMD\$004.B12.frm

105. (previously added) A point-to-multipoint optical communications system comprising:
an optical line terminal (OLT); and

a plurality of optical network units (ONUs) connected to said OLT by a passive optical network in which downstream data is transmitted from said OLT to said ONUs and upstream data is transmitted from said ONUs to said OLT;

said OLT including means for formatting downstream datagrams into variable-length downstream packets and a fragment buffer for storing packet fragments that have been transmitted upstream from said ONUs;

each of said ONUs including:

means for formatting upstream datagrams into variable-length upstream packets;

means for timing the transmission of said variable-length upstream packets to coincide with the ONU-specific time slots in order to avoid collisions with upstream packets from other ONUs;

fragment buffers for storing packet fragments that are to be transmitted upstream from said ONUs; and

fragment logic for:

splitting a variable-length upstream packet into first and second packet fragments; and

adding an end-of-packet fragment code to said first packet fragment and adding a start-of-packet-fragment code to said second packet fragment;

said OLT including fragment logic for:

identifying said end-of-packet-fragment code of said first packet fragment;

buffering said first packet fragment in said OLT fragment buffer;

identifying said start-of-packet-fragment code of said second packet fragment; and

reconstructing said variable-length upstream packet from said first and second packet fragments.

106. (previously added) The system of claim 105 wherein said variable-length downstream packets are formatted according to IEEE 802.3.

107. (previously added) The system of claim 105 wherein said downstream datagrams are Internet protocol (IP) datagrams.

108. (previously added) The system of claim 107 wherein the lengths of said variable-length downstream packets include the lengths of said IP datagrams plus packet overhead.

109. (previously added) The system of claim 105 wherein said variable-length upstream packets are formatted according to IEEE 802.3.

110. (previously added) The system of claim 105 wherein said upstream datagrams are Internet protocol (IP) datagrams.

111. (previously added) The system of claim 110 wherein the lengths of said variable-length upstream packets include the lengths of said IP datagrams plus packet overhead.

112. (previously added) The system of claim 105 wherein:
said variable-length downstream packets and said variable-length upstream packets are formatted according to IEEE 802.3; and

H:\HeidiE\Alloptic\AMD\$004.B12.frm

said downstream datagrams and said upstream datagrams are Internet protocol (IP) datagrams.

113. (previously added) A point-to-multipoint optical communications system comprising and optical line terminal (OLT); and

a plurality of optical network units (ONUs) connected to said OLT by a passive optical network in which downstream data is transmitted from said OLT to said ONUs over said passive optical network and upstream data is transmitted from said ONUs to said OLT over said passive optical network;

said OLT transmitting downstream data over said passive optical network in variable-length downstream packets and downstream synchronization markers at constant time intervals;

said ONUs transmitting upstream data over said passive optical network within ONU-specific time slots utilizing time division multiplexing, wherein said ONU-specific time slots are filled with multiple variable-length upstream packets.

said OLT includes:

a fragment buffer for storing packet fragments that have been transmitted upstream from said ONUs;

fragment logic for:

identifying said end-of-packet fragment code of said first packet fragment;

buffering said first packet fragment in said OLT fragment buffer;

identifying said start-of-packet-fragment code of said second packet fragment;

reconstructing said variable-length upstream packet from said first and second packet fragments;

H:\HeidiE\Alloptic\AMD\$004.B12.frm

said ONUs include:

fragment buffers for storing packet fragments that are
to be transmitted upstream from said ONUs;

fragment logic for:

splitting a variable-length upstream packet into
first and second packet fragments; and

adding an end-of-packet-fragment code to
said first packet fragment and adding a start-of-
packet fragment code to said second packet

fragment.

114. (previously added) The system of claim 113 wherein said variable-length downstream packets are formatted according to IEEE 802.3.

115. (previously added) The system of claim 113 wherein said variable-length downstream packets include Internet protocol (IP) datagrams.

116. (previously added) The system of claim 115 wherein the lengths of said variable length downstream packets includes the lengths of said IP datagrams plus packet overhead.

117. (previously added) The system of claim 113 wherein said variable-length upstream packets include Internet protocol (IP) datagrams.

118. (previously added) The system of claim 117 wherein the lengths of said variable-length upstream packets include the lengths of said IP datagrams plus packet overhead.

H:\HeidiE\Alloptic\AMD\$004.B12.frm

- 22 -

Ser. No. 09/715,275

119. (previously added) The system of claim 113 wherein;

said variable-length downstream packets and said variable-length upstream packets are formatted according to IEEE 802.3; and

said downstream data and said upstream data include Internet protocol (IP) datagrams.

H:\HeidiE\Alloptic\AMD\$004.B12.frm